AMP " PRO-SPORT" SPORT LOCKER (PRODUCT No. PSSL- _ _ _)

ELEVATION ' '



SIDE VIEW



FRONT VIEW

LOCKER DETAILS :

EXTERIOR COLOR =
INTERIOR COLOR = SAME AS EXTERIOR
TOP = FLAT
SECURITY BOX DOOR = PLAIN
HANDLES =FRICTION CATCH FINGER PULL
SIDE VENTILATION = 5/8" x 1-1/2" DIAMOND
LOCKS = PADLOCK OR BUILT-IN
BASE =
COAT ROD = 1" DIA. STAINLESS STEEL (OPT.)
HINGE = CONTINOUS FULL LENGTH PIANO HINGE WELDED TO BOX DOOR AND RIVETED TO FRAME

CONTRACTOR NOTE

ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4" FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL.

GAUGES

SECURITY BOX DOOR = 16 GA. C.R.S.
SEAT = 16 GA. C.R.S. (REINFORCED)
BASE = 16 GA., C.R.S.
TOP = 16 GA., C.R.S.
SHELF = 16 GA. C.R.S. (FULL DEPTH)
SIDE PANELS = 16 GA. C.R.S. (VENTED)
BACKS = 18 GA., C.R.S.

ART METAL PRODUCTS

THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF ART METAL, INC. AND SHALL NOT BE COPIED OR DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION. ONLY ART METAL RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES ART METAL FROM ALL LIABILITIES.

TOLERANCES UNLESS SPECIFIED:
FRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1°

Customer: CUSTOMER
Customer Order Number: PO#
Description: JOB NAME
JOB LOCATION

Drawn By:	Checked By:	Date:	Scale:
DRAFTER		DATE	NONE

Acad Number: PAGE NUMBER | Sheet # Of # | Revision:

Drawing Number: FOLDER NUMBER