

**Hallowell®**  
**High-Capacity Waterfall Boltless Shelving Specification**

**Finishing:** All shelving components to be cleaned and coated after fabrication with a seven stage zinc/iron phosphate solution to inhibit corrosion, followed by a coat of high grade custom blend powder electrostatically sprayed and baked at 350 degrees Fahrenheit for a minimum of 20 minutes to provide a tough durable finish.

**Color for all steel components:** Shall be Hallowell 708 Midnight Ebony (black).

Shelving shall be **GREENGUARD Children & Schools Certified<sup>SM</sup>**.

**Angle Post (Standard-Duty):** Shall be 1-1/2" x 1-1/2" x 14 gauge cold rolled steel corner post uprights.

**Double Rivet Angle Beam (Standard-Duty):** Shall be 2-3/4" x 1" x 16 gauge cold rolled steel. Typical for beams up to 36" in length.

**Double Rivet Angle Beam (Heavy-Duty):** Shall be 2-3/4" x 1" x 14 gauge cold rolled steel. An upgrade to our standard duty double rivet angle beams, our heavy duty double rivet angle beams provide additional unit rigidity and even higher shelf capacity. Typical for beams 48" long and greater.

**Center Support:** Shall be 2-3/4" x 1" x 1" x 16 gauge cold rolled steel. Used to provide additional shelf support front-to-back by bolting between double rivet beams at pre-punched locations.

**Steel Decking:** Shall be 14 gauge cold rolled sheet steel with flange formed at front and back designed to overhang left to right beams at front and back.

**One-Year Warranty:** HALLOWELL shelving is covered against all defects in materials and workmanship excluding finish, damage resulting from deliberate destruction and vandalism under this section **for a period of one year**.