## AMP "HEAVY DUTY CORRIDOR ELITE" K.D. DOUBLE TIER LOCKER (9" TO 15" WIDE) (PRODUCT No. HDCE -2) ELEVATION ' ' DOOR & FRAME COLOR = TOP = -STIFFENER SIDE VENTILATION = SOLID BASE = LOCKS = DOOR =

LOCKER DETAILS:

BODY COMPONENT COLOR = 729 PARCHMENT

HANDLE = LIFT (S.S. RECESSED DRAWN)

DOOR VENTILATION = 3' LOUVERS

HINGE = FULL LENGTH, STAKED PIAND

HINGE WELDED TO DOOR AND RIVETED TO FRAME

CONTRACTOR NOTE

ALL CONCRETE BASES SHOULD BE LEVEL AND TROVELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS, ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL.

## GAUGES

14 GA., C.R.S. STIFFENER = 18 GA., C.R.S. 16 GA., C.R.S FRAME = TOP = 24 GA., C.R.S. BOTTOM = 24 GA., C.R.S. SHELVES = 24 GA., C.R.S. SIDES = 24 GA., C.R.S. BACKS = 24 GA., C.R.S.

LATCHING: (WARDROBE) TWO POINT RECESSED AUTO-MATIC LOCKING DEVICE WITH LIFT-TYPE PADLOCK HASP, 36" TO 20" TALL DOORS.

SIDE VIEW

FRONT VIEW

## ART METAL PRODUCTS

THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF ART METAL, INC. AND SHALL NOT BE COPIED OR DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION. ONLY ART METAL RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES ART METAL FROM ALL LIABILITIES. TOLERANCES UNLESS SPECIFIED FRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1°

Drawn By: Checked By: Customer: CUSTOMER DRAFTER DATE Customer Order Number: PO# Sheet # Of # Revision: Acad Number: PAGE NUMBER Description: JOB NAME Drawing Number: FOLDER NUMBER JOB LOCATION

NONE

Scale: