# AMP "HEAVY DUTY CORRIDOR ELITE" K.D. TRIPLE TIER LOCKER (9" TO 15" WIDE) (PRODUCT No. HDCE -3) ELEVATION ' ' -STIFFENER SIDE VIEW FRONT VIEW

# LOCKER DETAILS:

DOOR & FRAME COLOR =

BODY COMPONENT COLOR = 729 PARCHMENT

TOP =

HANDLE = LIFT (S.S. RECESSED DRAWN)

DOOR VENTILATION = 3' LOUVERS

SIDE VENTILATION = SOLID

BASE = LOCKS =

HINGE = FULL LENGTH, STAKED PIAND HINGE WELDED TO DOOR AND RIVETED TO FRAME

### CONTRACTOR NOTE

ALL CONCRETE BASES SHOULD BE LEVEL AND TROVELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE OF THE BASE. LOCKERS WUST BE ANCHORED TO WALL.

## GAUGES

DOOR = 14 GA, C.R.S.
STIFFENER = 18 GA, C.R.S.
FRAME = 16 GA, C.R.S.
TOP = 24 GA, C.R.S.
BOTTOM = 24 GA, C.R.S
SHELVES = 24 GA, C.R.S
SIDES = 24 GA, C.R.S
BACKS = 24 GA, C.R.S.

LATCHING: (WARDROBE) TWO POINT RECESSED AUTO-MATIC LOCKING DEVICE WITH LIFT-TYPE PADLOCK HASP. 36' TO 20' TALL DOORS.

# ART METAL PRODUCTS

THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF ART METAL, INC. AND SHALL NOT BE COPIED OR DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION. DNLY ART METAL RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES ART METAL FROM ALL LIABILITIES.

TOLERANCES UNLESS SPECIFIED:
FRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1\*

Checked By: Date: Customer: CUSTOMER Drawn By: Scale: NONE DRAFTER DATE Customer Order Number: PO# Acad Number: PAGE NUMBER Sheet # Of # Revision: Description: JOB NAME Drawing Number: FOLDER NUMBER JOB LOCATION