AMP "HEAVY DUTY VENTILATED" K.D. ATHLETIC TRIPLE TIER LOCKER (9" TO 15" WIDE) (PRODUCT No. HDV _ _ _ _ _ _ -3_)

# ELEVATION ' '




SIDE VIEW




FRONT VIEW

## LOCKER DETAILS:

DOOR & FRAME COLOR =
BODY COMPONENT COLOR = 729 PARCHMENT OR 725 HALLOWELL GRAY
TOP =
HANDLE = LIFT (S.S. RECESSED DRAWN)
DOOR VENTILATION = 5/8" x 1-1/2" DIAMOND
SIDE VENTILATION = 5/8" x 1-1/2" DIAMOND
BASE =
LOCKS =
HINGE = CONTINUOUS PIANO HINGE

CONTRACTOR NOTE

ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4" FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL.

## GAUGES

DOOR = 14 GA., C.R.S.
FRAME = 16 GA., C.R.S
TOP = 16 GA., C.R.S.
BOTTOM = 16 GA., C.R.S.
SHELVES = 16 GA., C.R.S.
SIDES = 16 GA., C.R.S.
BACKS = 18 GA., C.R.S.

LATCHING: (WARDROBE) TWO POINT RECESSED AUTO-MATIC LOCKING DEVICE WITH LIFT-TYPE PADLOCK HASP. 36" TO 20" TALL DOORS.

**ART METAL PRODUCTS**

THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF ART METAL, INC. AND SHALL NOT BE COPIED OR DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION. ONLY ART METAL RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES ART METAL FROM ALL LIABILITIES.

TOLERANCES UNLESS SPECIFIED:
FRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1°

Customer: CUSTOMER
Customer Order Number: PO#
Description: JOB NAME
JOB LOCATION

| Drawn By: | Checked By: | Date: | Scale: |
|---|---|---|---|
| DRAFTER | | DATE | NONE |
| Acad Number: PAGE NUMBER | | Sheet # Of # | Revision: |
| Drawing Number: FOLDER NUMBER | | | |