AMP 'MAGNUM STUDENT' K.D. TRIPLE TIER LOCKER (9' TO 15' WIDE) (PRODUCT No. AMS -3) ELEVATION ' - STIFFENER :

I TICKER DETAILS:

DOOR & FRAME COLOR =

BODY COMPONENT COLOR = 729 PARCHMENT

TOP :

HANDLE = SINGLE POINT (S.S. RECESSED DRAWN)

DOOR VENTILATION = PLAIN

(OPTIONAL SECURE-AIR-FLOW)

SIDE VENTILATION = SOLID

BASE =

LOCKS =

HINGE = FULL LENGTH, STAKED PIAND HINGE WELDED TO DOOR &

RIVETED TO FRAME

CONTRACTOR NOTE

ALL CONCRETE BASES SHOULD BE LEVEL AND TROVELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE OF THE BASE. LICKERS MUST BE ANCHORED TO WALL.

GAUGES

DIOR = 14 GA, C.R.S.
STIFFENER = 18 GA, C.R.S.
FRAME = 16 GA, C.R.S.
BUTTOM = 24 GA, C.R.S.
SHELVES = 24 GA, C.R.S.
SIDES = 24 GA, C.R.S.
BACKS = 24 GA, C.R.S.

LATCHING: (WARDROBE) SINGLE POINT RECESSED

LOCKING DEVICE PREPARED FOR BOTH

PADLOCK AND BUILT-IN LOCKS.

SIDE VIEW

FRONT VIEW

ART METAL PRODUCTS

THIS DRAVING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF ART METAL, INC. AND SHALL NOT BE COPIED OR DISCLOSED TO DITHER VITHOUT VETTEN PERMISSION. ONLY ART METAL RESERVES THE RIGHT TO ALTER ANY DESIGN ANY UNAUTHORIZED MODIFICATIONS RELEASES ART METAL FROM ALL LIABILITIES.

TOLERANCES UNLESS SPECIFIED.

TOLERANCES UNLESS SPECIFIED:
FRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1*

 Customer: CUSTOMER
 Drawn By: DRAFTER
 Checked By: DRAFTER
 Date: DATE
 NONE

 Customer Order Number: PO#
 Acad Number: PAGE NUMBER
 Sheet # Of # Revision:

 Description: JOB NAME JOB LOCATION
 Drawing Number: FOLDER NUMBER