

AMP 'MAGNUM STUDENT' K.D. TRIPLE TIER LOCKER (18' TO 24' WIDE) (PRODUCT No. AMS -3)

ELEVATION ' '





INCKER DETAILS:

DOOR & FRAME COLOR =

BODY COMPONENT COLOR = 729 PARCHMENT

TOP :

HANDLE = SINGLE POINT (S.S. RECESSED DRAWN)

DOOR VENTILATION = PLAIN

(OPTIONAL SECURE-AIR-FLOW)

SIDE VENTILATION = SOLID

BASE = LOCKS =

HINGE = FULL LENGTH, STAKED PIAND

HINGE WELDED TO DOOR & RIVETED TO FRAME

CONTRACTOR NOTE

ALL CONCRETE BASES SHOULD BE LEVEL AND TROVELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL.

GAUGES

DOOR = 14 GA, C.R.S.
STIFFENER = 18 GA, C.R.S.
FRAME = 16 GA, C.R.S.
BUTTOM = 24 GA, C.R.S.
SHELVES = 24 GA, C.R.S.
SIDES = 24 GA, C.R.S.
BACKS = 24 GA, C.R.S.

LATCHING: (WARDROBE) SINGLE POINT RECESSED
LOCKING DEVICE PREPARED FOR BOTH
PADLOCK AND BUILT-IN LOCKS.

SIDE VIEW

FRONT VIEW

ART METAL PRODUCTS

THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF ART METAL, INC. AND SHALL NOT BE COPIED OR DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION, ONLY ART METAL RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES ART METAL FROM ALL LIABILITIES.

TOLERANCES UNLESS SPECIFIED:

TRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1°

Revision:

NONE