AMP "STANDARD K.D." DOUBLE TIER LOCKER (9" TO 15" WIDE) (PRODUCT No. SK -2) INCKER DETAILS: ELEVATION ' ' DOOR & FRAME COLOR = BODY COMPONENT COLOR = 729 PARCHMENT TOP = HANDLE = LIFT (S.S. RECESSED DRAWN) D DOOR VENTILATION = 3' LOUVERS SIDE VENTILATION = SOLID BASE = LOCKS = HINGE = CONTINUOUS PIAND HINGE CONTRACTOR NOTE ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS, ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL. GAUGES DOOR = 16 GA., C.R.S. (9" WIDE DOOR = 18 GA., C.R.S.) FRAME = 16 GA., C.R.S TOP = 24 GA., C.R.S. BDTTDM = 24 GA., C.R.S.SHELVES = 24 GA., C.R.S. SIDES = 24 GA., C.R.S. : BACKS = 24 GA., C.R.S. LATCHING: (WARDROBE) TWO POINT RECESSED ON LOCKER DOORS **言**言 ON LOCKER DOORS 36" TO 20". AUTOMATIC AUTOMATIC LOCKING DIVICE WITH LIFT-TYPE PADLOCK HASP. SIDE VIEW FRONT VIEW THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF ART METAL, INC. AND SHALL NOT BE COPIED OR Checked By: Drawn By: Date: Customer: CUSTOMER NONE DRAFTER DATE DISCLOSED TO OTHERS VITHOUT VRITTEN PERMISSION. DNLY ART METAL RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES ART METAL FROM ALL LIABILITIES. Customer Order Number: PO# ART METAL PRODUCTS Acad Number: PAGE NUMBER Sheet # Of # Revision: Description: JOB NAME Drawing Number: FOLDER NUMBER TOLERANCES UNLESS SPECIFIED JOB LOCATION FRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1°