AMP "STANDARD K.D." TWO PERSON LOCKER (15" TO 18" WIDE) (PRODUCT No. SK -2P) ELEVATION ' ' DOOR & FRAME COLOR = TOP = SIDE VENTILATION = SOLID BASE = RIGHT HINGED LOCKS = HINGE = CONTINUOUS PIANO HINGE LEFT HINGED CONTRACTOR NOTE GAUGES RIGHT HINGED 18 GA., C.R.S. DOOR = 16 GA., C.R.S FRAME = TOP = 24 GA., C.R.S. BOTTOM = 24 GA., C.R.S. SHELVES = 24 GA., C.R.S. SIDES = 24 GA., C.R.S. BACKS = 24 GA., C.R.S. LEFT HINGED SIDE VIEW FRONT VIEW THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF ART METAL, INC. AND SHALL NOT BE COPIED OR Checked By: Drawn By: Date: Customer: CUSTOMER

LOCKER DETAILS:

BODY COMPONENT COLOR = 729 PARCHMENT

HANDLE = LIFT (S.S. RECESSED DRAWN)

DOOR VENTILATION = 3' LOUVERS

ALL CONCRETE BASES SHOULD BE LEVEL AND TROVELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL.

LATCHING: (WARDROBE) TWO POINT RECESSED AUTO-MATIC LOCKING DEVICE WITH LIFT-TYPE PADLOCK HASP, 36" TO 20" TALL DOORS.

ART METAL PRODUCTS

DISCLOSED TO OTHERS VITHOUT VRITTEN PERMISSION. DNLY ART METAL RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES ART METAL FROM ALL LIABILITIES. TOLERANCES UNLESS SPECIFIED FRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1°

NONE DRAFTER DATE Customer Order Number: PO# Acad Number: PAGE NUMBER Sheet # Of # Revision: Description: JOB NAME Drawing Number: FOLDER NUMBER JOB LOCATION