AMP 'STANDARD' K.D. SAFETY-VIEW DOUBLE TIER LOCKER (12' WIDE) (PRODUCT No. SK -2SV) LOCKER DETAILS: ELEVATION ' ' DOOR & FRAME COLOR = BODY COMPONENT COLOR = 729 PARCHMENT TOP = HANDLE = LIFT (S.S. RECESSED DRAWN) DOOR = (2) POLYCARBONATE WINDOWS SIDE VENTILATION = SOLID BASE = LOCKS = HINGE = CONTINUOUS PIANO HINGE CONTRACTOR NOTE ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE OF THE BASE, LOCKERS MUST BE ANCHORED TO WALL. GAUGES 16 GA., C.R.S. DOOR = 16 GA., C.R.S FRAME = TOP = 24 GA., C.R.S. BOTTOM = 24 GA., C.R.S. SHELVES = 24 GA., C.R.S. 24 GA., C.R.S. SIDES = BACKS = 24 GA., C.R.S. LATCHING: (WARDROBE) TWO POINT RECESSED AUTO-MATIC LOCKING DEVICE WITH LIFT-TYPE PADLOCK HASP. 36" TO 20" TALL DOORS. HINGES: (WARDROBE) TWO HINGES ON LOCKER DOORS 36" AND UNDER. SIDE VIEW FRONT VIEW THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF ART METAL, INC. AND SHALL NOT BE COPIED OR Checked By: Drawn By: Date: Customer: CUSTOMER NONE DRAFTER DATE DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION. ONLY ART METAL Customer Order Number: PO# ART METAL PRODUCTS RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES ART METAL FROM ALL LIABILITIES. Acad Number: PAGE NUMBER Sheet # Of # Revision: Description: JOB NAME Drawing Number: FOLDER NUMBER TOLERANCES UNLESS SPECIFIED JOB LOCATION FRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1°