AMP "STANDARD QUIET" K.D. TRIPLE TIER LOCKER (9" TO 15" WIDE) (PRODUCT No. SQ -3) LOCKER DETAILS: ELEVATION ' ' DOOR & FRAME COLOR = TOP AND BOTTOM BODY COMPONENTS COLOR = 729 PARCHMENT TOP = CONCEALED HANDLE = LIFT (S.S. RECESSED DRAWN) FLANGE VENTILATION DOOR VENTILATION = SOLID SIDE VENTILATION = SOLID BASE = LOCKS = HINGE = CONTINUOUS PIANO HINGE CONTRACTOR NOTE ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS, ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4" FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL. • • GAUGES 16 GA., C.R.S. DOOR = (9" WIDE DOOR = 18 GA., C.R.S.) : 16 GA., C.R.S FRAME = 24 GA., C.R.S. TOP = $B\Box TT\Box M = 24 GA., C.R.S.$ SHELVES = 24 GA., C.R.S. SIDES = 24 GA., C.R.S. • BACKS = 24 GA., C.R.S. LATCHING: (WARDROBE) TWO POINT RECESSED AUTO-MATIC LOCKING DEVICE WITH LIFT-TYPE PADLOCK HASP, 36" TO 20" TALL DOORS. SIDE VIEW FRONT VIEW THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF ART METAL, INC. AND SHALL NOT BE COPIED OR Checked By: Drawn By: Customer: CUSTOMER DRAFTER NONE DATE DISCLOSED TO DITHERS WITHOUT WRITTEN PERMISSION, ONLY ART METAL RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES ART METAL FROM ALL LIABILITIES. Customer Order Number: PO# ART METAL PRODUCTS Sheet # Of # Revision: Acad Number: PAGE NUMBER Description: JOB NAME Drawing Number: FOLDER NUMBER TOLERANCES UNLESS SPECIFIED JOB LOCATION FRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1*