## AMP-1003 "CHAMP" CORRIDOR SINGLE TIER LOCKER (9" TO 15" WIDE) (PRODUCT No. AWC -1) LOCKER DETAILS: ELEVATION ' ' EXTERIOR COLOR = INTERIOR COLOR = SAME AS EXTERIOR TNP = HANDLE = LIFT (S.S. RECESSED DRAWN) DOOR VENTILATION = 3' LOUVER SIDE VENTILATION = SOLID BASE = LOCKS = HINGE = FULL LENGTH, STAKED PIAND HINGE WELDED TO DOOR & 12,312 RIVETED TO FRAME CONTRACTOR NOTE all concrete bases should be level and troweled smooth to assure proper installation of the lockers. All FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE THE BASE. LITCKERS MUST BE ANCHORED TO WALL. GAUGES DDDR = 14 GA., C.R.S.FRAME = 16 GA., C.R.S TDP = 16 GA., C.R.S.BOTTOM BASE = 16 GA., C.R.S.SHELVES = 16 GA., C.R.S. SIDES = 16 GA., C.R.S. BACKS = 18 GA., C.R.S. LATCHING: (WARDROBE) THREE POINT RECESSED ON LOCKER DOORS 48" AND OVER, TWO POINT RECESSED ON ON LOCKER DOORS 36" TO 20". AUTOMATIC LOCKING DEVICE WITH LIFT-TYPE PADLOCK HASP. FRONT VIEW SIDE VIEW THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF ART METAL, INC. AND SHALL NOT BE COPIED OR DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION. ONLY ART METAL RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES ART METAL FROM ALL LIABILITIES. Checked By: Drawn By: Customer: CUSTOMER DRAFTER DATE NONE Customer Order Number: PO# ART METAL PRODUCTS Revision: Acad Number: PAGE NUMBER Sheet # Of # Description: JOB NAME Drawing Number: TOLERANCES UNLESS SPECIFIED FOLDER NUMBER JOB LOCATION FRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1\*