AMP-1003 "CHAMP" CORRIDOR DOUBLE TIER LOCKER (9" TO 15" WIDE) (PRODUCT No. AWC -2) I TICKER DETAILS: ELEVATION ' EXTERIOR COLOR = INTERIOR COLOR = SAME AS EXTERIOR TIP = HANDLE = LIFT (S.S. RECESSED DRAWN) DOOR VENTILATION = 3' LOUVER SIDE VENTILATION = SOLID BASE = LOCKS = HINGE = FULL LENGTH, STAKED PIAND HINGE WELDED TO DOOR & RIVETED TO FRAME CONTRACTOR NOTE ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL ٥ FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4" FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL. GAUGES 14 GA., C.R.S. DOOR = FRAME = 16 GA., C.R.S 16 GA., C.R.S. TTP = BOTTOM BASE = 16 GA., C.R.S. SHELVES = 16 GA., C.R.S. SIDES = 16 GA., C.R.S. 18 GA., C.R.S. BACKS = LATCHING: (WARDROBE) TWO POINT RECESSED AUTO-MATIC LOCKING DEVICE WITH LIFT-TYPE PADLOCK HASP, 36' TO 20' TALL DOORS. FRONT VIEW SIDE VIEW THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF ART METAL, INC. AND SHALL NOT BE COPIED OR DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION. DNLY ART METAL RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES ART METAL FROM ALL LIABILITIES. Checked By: Drawn By: Customer: CUSTOMER NONE DRAFTER DATE ART METAL PRODUCTS Customer Order Number: PO# Sheet # Of # Revision: Acad Number: PAGE NUMBER Description: JOB NAME Drawing Number: FOLDER NUMBER TOLERANCES UNLESS SPECIFIED JOB LOCATION DEGREES: ±1* FRACTIONS: ±1/32 DECIMALS: ±.010