AMP-1003E "CHAMP" ELITE CORRIDOR TRIPLE TIER LOCKER (18" OR 24" WIDE) (PRODUCT No. AEC _ _ _ -3) LOCKER DETAILS: ELEVATION EXTERIOR COLOR = INTERIOR COLOR = SAME AS EXTERIOR TOP = HANDLE = LIFT (S.S. RECESSED DRAWN) DOOR VENTILATION = 3' LOUVER STIFFENER SIDE VENTILATION = SOLID BASE = LOCKS = HINGE = FULL LENGTH, STAKED PIAND HINGE WELDED TO DOOR & RIVETED TO FRAME CONTRACTOR NOTE ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL. GAUGES • • DOOR = 14 GA., C.R.S. 18 GA., C.R.S. STIFFNER = FRAME = 16 GA., C.R.S TOP = 16 GA., C.R.S. BOTTOM BASE = 16 GA., C.R.S. 16 GA., C.R.S. SHELVES = 16 GA., C.R.S. SIDES = BACKS = 18 GA., C.R.S. · • **量 三** LATCHING: (WARDROBE) TWO POINT RECESSED AUTO-MATIC LOCKING DEVICE WITH LIFT-TYPE PADLOCK HASP. 36" TO 20" TALL DOORS. \equiv SIDE VIEW FRONT VIEW THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL Checked By: Drawn By: Date: Customer: CUSTOMER PROPERTY OF ART METAL, INC. AND SHALL NOT BE COPIED OR DRAFTER NONE DATE DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION. ONLY ART METAL RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES ART METAL FROM ALL LIABILITIES. Customer Order Number: PO# ART METAL PRODUCTS Acad Number: PAGE NUMBER Sheet # Of # Revision: Description: JOB NAME Drawing Number: FOLDER NUMBER TOLERANCES UNLESS SPECIFIED

FRACTIONS: ±1/32

DECIMALS: ±.010

DEGREES: ±1°

JOB LOCATION