LOCKER DETAILS: AMP "PRO-SPORT" WELDED SPORT LOCKER (PRODUCT No. PSTN-) EXTERIOR COLOR = INTERIOR COLOR = SAME AS EXTERIOR TOP = FLAT ELEVATION ' ' SECURITY BOX - TOP HINGED 14 GA. WITH SPRING BOLT LATCH AND SECURE-AIR-FLOW VENTITATION LOCKS = PADLOCK OR BUILT-IN HINGE = CONCEALED ROD (SECURITY BOX) SIDE VENTILATION = 5/8" x 1-1/2" DIAMOND BASE = COAT ROD = 1' STAINLESS STEEL (OPTIONAL) 13" CONTRACTOR NOTE ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS, ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL. GAUGES **OPTIONAL** COAT ROD DOOR = 14 GA., C.R.S. BASE = 16 GA., C.R.S. TDP = 16 GA., C.R.S.SHELF = 16 GA., C.R.S. (FULL DEPTH) SIDE PANELS = 16 GA. (VENTED) BACKS = 18 GA., C.R.S. SIDE VIEW FRONT VIEW THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL Drawn By: Checked By: Date: Customer: CUSTOMER PROPERTY OF ART METAL, INC. AND SHALL NOT BE COPIED OR NONE DRAFTER DATE DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION. ONLY ART METAL Customer Order Number: PO# ART METAL PRODUCTS RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES ART METAL FROM ALL LIABILITIES. Acad Number: PAGE NUMBER Sheet # Of # Revision: Description: JOB NAME Drawing Number: FOLDER NUMBER TOLERANCES UNLESS SPECIFIED JOB LOCATION FRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1°